

HERO is our new residential heat recovery units designed to perform even at very low temperatures. With its 85%+ efficient rotary system and by transferring humidity, it gives optimum indoor experience for our living spaces.

Smooth Operation

With its very compact and double skin casing, it has very quiet and convenient operation.

Easy Service

Filters and all other servicable parts can be reached easily from the bottom panel.

















EASY INSTALLATION

LOW SERVICE COST

www.eneko.com.tr

Factory: 10049 St. No: 4 I.A.O.S.B. Cigli/Izmir - Turkiye - 0232 328 20 80 - 0232 328 20 22 - export@eneko.com.tr Istanbul Sales Office: Cevizli District, Zuhal Avenue, Fusun St., Ritim Istanbul A5 Block Floor: 25 No: 137, 34846 Maltepe/ Istanbul - Turkiye 0216 455 29 60 - 0216 455 29 61 - 0216 455 29 62 - satis@eneko.com.tr



TECHNICAL SPECIFICATIONS

	Hero 300	Hero 600
Weight (kg)	36	45
Width (mm)	530	650
Lenght (mm)	700	800
Height (mm)	340	340
Air flow (m3/h)	300	600
Duct Pressure (Pa)	100	100
HR Efficiency @Nominal Flow	80,5%	80%
Total Power Input (Watt)	235	495

Control & Accessories

SENSORS

- As option, unit can be equipped with ${\rm CO_2}$ and RH sensors.

ENECON PLUS PANEL

- Enecon Plus Panel where the user can select ventilation speeds.
- User friendly 3.1" display
- Weekly timer

Standard Features

- Heat exchanger efficiency (Up to 85%)
- Coarse 65% (G4)
- Free cooling

Optional Features

- Airflow control
- Humidity control
- CO₂ control
- SA temperature sensor
- Proportional heating/cooling coil
- On/off heating/cooling coil
- Electrical pre/after heater
- ePM1 >50% (F7), ePM10 >50%(M5)



